

SQUASH COURT

Handy tips

Clean Down:

Wash black rubber ball marks off with Mineral Turps and a clean cloth.

Wash dirty marks off playing area with approx. 20mls dish washing detergent and a bucket of warm water. Note... a rectangle bucket is ideal along with a swivel scouring pad holder on an extension pole. Rinse with fresh warm water, wipe down with a dry clean cloth.

Repair:

Front playing wall if patching is required;

Firstly dig out loose material and dust down, apply one coat of Duralex Surface Binder, and allow to dry for 2 hours.

We recommend an exterior cement based filler, containing acrylic dispersible powder. Follow mixing instructions on pack. Apply with spatula; finish off with a wood float trowel to give a rendered sandy finish appearance. Allow to cure.

Paint:

Spot prime bare patches with either Duralex 3 in 1 Primer/Undercoat or Duralex Premium Undercoat, one coat should be sufficient, allow to dry. Finish off with 2 coats of Duralex Squash Court, allowing 2 hours between coats.

Note. To assist drying open where possible, all windows and doors whilst painting to provide cross ventilation or employ an fan to circulate fresh air around the court to dissipate water vapour. Paint one day play next day!

Duralex Squash Court is Low Odour and Low VOC allowing the other courts to remain open.

Did you know?!

Duralex also offers Red Line marking tape 33m x 48mm rolls.

