



DURALEX®

Timber Care

PRODUCT INFORMATION SHEET

dura-COAT®

DESCRIPTION

Duralex dura-COAT® is a durable semi-gloss 100% acrylic wood finish. dura-COAT® will not flake or peel and has extremely good resistance to weathering. It is not recommended for timber decking; use Duralex hydra-DECK® for these areas.

PREPARATION

ALL SURFACES INCLUDING NEW BARE TIMBER, OLD BARE TIMBER, PREVIOUSLY STAINED SURFACES AND PREVIOUSLY PAINTED SURFACES:

The surface to be coated must be thoroughly dry, free of oil and wax and be well sanded. Coarse sand with 120 grit to 400 grit for best results. Always sand in the direction of the grain. Remove all dust, wipe down with a damp, lint free cloth and allow to dry. Cracks, holes and knots if desired should be filled with a suitable wood filler and allowed to dry.

APPLICATION

Always apply a small test panel to underside or obscure position of project or scrap of timber to check colour and porosity. Do not attempt project in damp or humid weather.

ROUGH SAWN TIMBER: dura-COAT® is best applied by brush finishing off along the grain.

DRESSED TIMBER: dura-COAT® can be applied by brush, roller, painters pad and/or spray.

Apply a minimum of 2 liberal coats or more depending on depth of desired colour and finish. Allow adequate cross ventilation indoors to dissipate moisture.

DRYING TIME

In average weather conditions (25°C), touch dry in 20 mins. If surface looks patchy after 2 coats, apply a 3rd coat after 2 hours. Surface area must be above 10°C during application and drying time.

CLEAN UP

Clean equipment and spills with water immediately after use. Use Methylated Spirits for dried spots.

IMPORTANT NOTES and DISPOSAL

Paint container must be properly sealed at all times when not in use. Do not pour leftover product down drain. Wash all

equipment with clean water. (See Product Information Sheet for disposal).

Note: Never allow waste water to enter storm water drains or sewers.

SIZES

15, 10, 4, 1 Litre & 500mL.

RECYCLE

This can is recyclable. Check with your local council to see if it is participating in a steel can-recycling programme.

ENVIRONMENT

Low odour. Low V.O.C. Environmentally friendly.

IMPORTANT

Keep out of reach of children. If contact with the eyes occurs, rinse with running water and seek help if irritation persists. If swallowed, do not induce vomiting. Give a glass of water and seek medical assistance or contact the Poison Information Centre (13 11 26).



The information given herein is believed to be accurate and reliable but is presented without guarantee, warranty or responsibility of any kind. Users of our products should perform their own tests to determine the suitability of each Duralex product for their particular purposes. This information is being constantly updated and subject to change without notice.

DURALEX
ENVIRONMENTALLY
AWARE

3-5 Muriel Avenue, Rydalmere N.S.W. 2116
PHONE: (02) 9638 0568 FAX: (02) 9684 1864

www.duralexpaints.com.au

NEVER POUR LEFTOVER PAINTS DOWN THE DRAIN

CLEANING UP AFTER PAINTING

(Industry standard for Water-based paint)

EXCESS/UNWANTED PAINT

- At the completion of a painting job, pour, brush or roll excess unwanted paint onto an absorbent material such as kitty litter, old rags, newspaper, cardboard, etc.
- Allow paint to dry, this could take up one week, then dispose with household waste collection services.

WASHING OF EQUIPMENT: (Two-Container Method)

- **20 Litre containers are best!**
- Wash brushes, rollers and other equipment in the FIRST container of water.
- Transfer the washed equipment to the SECOND container filled with clean water for a final rinse.
- Allow the containers to stand, overnight the paint solids will settle to the bottom, this usually takes about 12 hours. The clear water from the FIRST container may now be poured on the garden where it will be absorbed into the ground. Avoid areas near drains, streams, rivers or lakes.

DISPOSAL OF RESIDUE:

- Paint solids at the bottom of the first container can be scraped onto an absorbent material as previously described. Allow to dry, then dispose as previously described.
- The SECOND container can now be used as the first wash. Follow this cleaning system until the job is completed.

CAUTION:

- Never allow waste water to enter household storm water drains or sewers.

DISPOSAL OF LEFTOVER PAINT CONTAINERS

EMPTY OUT CONTAINER

Ensure paint container is as clean as possible.

RECYCLE STEEL CONTAINER

- The cleaned paint container can be disposed of via local steel recycling programs (check with your local Council).